

105128H

1/2 HP

**DEEP WELL
SUBMERSIBLE PUMP**

**Pumps up to 840 US GPH
Maximum Head of 250 Feet**

**3 WIRE + GROUND / 230V
6 STAGES**



**10
GPM**



PUMP CAPACITY

| HEAD | LPH | US GPH |
|------|-------|--------|
| 250' | 76,0m | 380 |
| 225' | 68,5m | 985 |
| 200' | 61,0m | 1325 |
| 180' | 55,0m | 1590 |
| 160' | 49,0m | 1855 |
| 140' | 43,0m | 2160 |
| 120' | 36,5m | 2460 |
| 100' | 30,5m | 2690 |
| 80' | 24,5m | 2955 |
| 60' | 18,5m | 3180 |

Friction loss in pipe not included

Best efficiency

| Pressure switch set to : | Depth : |
|--------------------------|-----------|
| 20/40 PSI | 27' - 81' |
| 30/50 PSI | 5' - 58' |

- Made of non-corrosive 304 stainless steel material
- Precision machined Noryl impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Stainless steel shell and drive shaft

Recommended for homes, cottages and farms for installation in water wells which are 4'' and larger in diameter.

Control box included.



Water in
PUMP SYSTEM

