

**Noryl pump body and ejector  
to prevent rust contamination.**



506727PSS

# 3/4 HP

## NORYL CONVERTIBLE JET PUMP SYSTEM

	Shallow Well	Deep Well
Pumps up to :	800 US GPH	675 US GPH
Maximum vertical suction lift	25 Feet	80 Feet



### PUMP CAPACITY

LIFT	LPH	US GPH
Deep Well Operation		
80' 24,5m	475	125
70' 21,0m	750	200
30' 9,0m	2550	675
Shallow Well Operation		
25' 7,5m	1135	300
5' 1,5m	3025	800

Friction loss in pipe not included

- 1 1/4" suction
- 1" discharge



**Recommended for  
home, cottage and  
farm applications**

### DESCRIPTION

- 7 US gallon stainless steel air pressure tank
- No water-air contact
- No water-tank contact
- Noryl pump body.
- 115/230V (9.0/4.5A) motor, totally enclosed fan-cooled.
- Bearing to bearing stainless steel motor shaft.
- Full-time running capacitor.
- Stainless steel mechanical seal.

### OPERATION

- In conjunction with a pressure tank, the pressure switch turns the pump on when the pressure drops below 30 PSI and turns the pump off when the pressure rises up to 50 PSI.



Water in  
PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)

